




Typical Dual Frequency Connectors (50/200 kHz)


The last part of the transducer part number indicates the connector that is supplied. Please note that these connectors are common to a given manufacturer and do not necessarily mean a transducer will work with your unit.


Model **B164-20-10F** Connector
Tilt


Airmar®	-0	
	Connector: None, Depth and temperature Fits: Bare wire applications	


Lowrance®	-BL	
	Connector: 7-pin, Depth and temperature Fits: Units with blue or gray connector	


Airmar®	-3	
	Connector: 3-pin Fuji, Depth only Fits: Older units with 3-pin Fuji connector	


Northstar®	-6NAV	
	Connector: 6-pin, Depth and temperature Fits: Northstar 50/200 kHz M Series	


Airmar®	-8	
	Connector: 8-pin Fuji, Depth and temperature Fits: Furuno and Si-Tex 8-pin Fuji connector	


Navman®	-6NAV	
	Connector: 6-pin, Depth and temperature Fits: Navman 6-pin	


Extension	-5P-5P	
	Connector: 5P/5P extension Fits: 12 m (40') extension cable for mix &match	


Navico®	-2CN	
	Connector: 2-pin, Depth only Fits: Certek and Navico	


Autohelm®	-2	
	Connector: 2-pin, Depth only Fits: Autohelm ST50 only	


Navico®	-9N	
	Connector: 9-pin, Depth only Fits: HDS Carbon, evo 3	


Datamarine®	-RCA	
	Connector: RCA, Depth only Fits: Datamarine, Navman, Vertex Standard	


Northstar®	-10NS	
	Connector: 10-pin, Depth and temperature Fits: 490S, 491 (600W)	


Furuno®	-10F	
	Connector: 10-pin, Depth and temperature Fits: All Furuno 10-pin units	


Raymarine®	-FISO	
	Connector: Spade, Depth only Fits: ST30, 40, 60, i40, i50, i60	


Garmin®	-6DO	
	Connector: 6-pin, Depth only Fits: Garmin depth only applications	


Raymarine®	-RAY	
	Connector: Radar, Depth and temperature Fits: L755,760,770,1250, DSM 30,250,300, CP370	


Garmin®	-6G	
	Connector: 6-pin, Depth and temperature Fits: Garmin 6-pin Depth and temp. applications	


Raymarine®	-RAYA	
	Connector: 6/9 Pin, Depth and temperature Fits: "A" series: DS400X, DS500X, DS600X, A50D, A57D, A65D, A70D, DSM25, a65, a67, e7D, c97, e97, c127, e127	


Garmin®	-8G	
	Connector: 8-pin, Depth and temperature Fits: Garmin GSD24, "xs" series	

Simrad®	-7	
	Connector: 7-pin, Depth and temperature Fits: Simrad, Raytheon, and JRC	

Humminbird®	-18HB	
	Connector: 8-pin, Depth and temperature Fits: Humminbird sounder applications	

Simrad®	-6NAV	
	Connector: 6-pin, Depth and temperature Fits: Simrad NX 40/45	

Humminbird®	-HB	
	Connector: #9, Depth and temperature Fits: All 800, 900 and 1100 series except 9673D	

Sitex®	-8S	
	Connector: 8-pin, Depth and temperature Fits: CVS 126/128, SVS 650/750, CVS 1410	