13 mm Micro: CB Cars

Harken Micro CB traveler cars are used on small dinghies and catamarans.

About CB traveler cars: see feature pages at beginning of this section.



Carbo T2 blocks attached with high-tech line provide the ultimate lightweight, low-profile system.

Loop cars matched with 29 or 40 mm

Block not included



Pivoting shackle cars have low pivot points to handle nonvertical loads.











16 mm control blocks spin on stainless steel balls that roll freely under high loads. The step-down design keeps the controls low and clear of the mainsheet block.

CAR CONTROLS

Cars

CARS

Part		Length		Width		Car body height		Weight		Maximum working load		Breaking load	
No.	Description	in	mm	in	mm	in	mm	0Z	g	lb	kg	lb	kg
2700	Pivoting shackle	2³/ ₁₆	56	19/16	40	3/4	19	1.76	50	310	140	1500	680
2701	Pivoting shackle/control blocks	37/16	87	19/16	40	3/4	19	2.56	73	310	140	1500	680
2702	Pivoting shackle/tangs	2³/s	61	1%16	40	3/4	19	2.08	59	310	140	1500	680
2703	Loop	23/16	56	1%	40	3/4	19	1.6	45	310	140	1500	680

See page 33 for replacement balls.

Car Controls

Part		Sh	Sheave Ø		Length		Weight		Max line Ø		Maximum working load		iking ad	
No.	Description	in	mm	in	mm	OZ	g	in	mm	lb	kg	lb	kg	Purchase
2704	Control block (pair)	5/8	16	15/16	33	.39	11	7/32	5	250	113	750	339	2:1
2705	Control tang (pair)	_	_	13/16	21	.11	3	_	_	250	113	750	339	1:1