

22 mm Small Boat: CB Cars

Small Boat CB traveler cars fit dinghies, keelboats, beachcats, and offshore boats to 8 m (27').

About CB traveler cars: see feature pages at beginning of this section.



Loop cars matched with 29 or 40 mm Carbo T2 blocks attached with high-tech line provide the ultimate lightweight, low-profile system.



Blocks attach directly to the toggle for a low-profile, compact system.

Pivoting shackle and toggle cars have low pivot points to handle nonvertical loads.

The 382 radial traveler car has a curved ball race to fit curved track—perfect for radial vang on boats like the Star.

Delrin is a registered trademark of E. I. du Pont de Nemours and Company or its affiliates.

Part No.	Description	Length		Width		Car body Height		Weight	Mainsheet block pin Ø		Control block pin Ø		Maximum working load		Breaking load		
		in	mm	in	mm	in	mm		oz	g	in	mm	in	mm	lb	kg	lb
382	High-load/radial/shackle†	4 1/8	105	2 1/4	57	1 9/16	24	6.24	177	—	—	—	—	1250	567	2500	1134
2726*	Low-load/pivoting shackle**	2 7/8	73	2 1/4	57	1 9/16	24	4.64	132	—	—	—	—	500	227	2500	1134
2727*	Pivoting shackle	2 7/8	73	2 1/4	57	1 9/16	24	4.64	132	—	—	—	—	850	386	2500	1134
2728	Low-load/fixed sheaves/eyestraps**	2 7/8	73	2 1/4	57	1 9/16	24	5.6	159	—	—	—	—	500	227	2500	1134
2729	Fixed sheaves/eyestraps	2 7/8	73	2 1/4	57	1 9/16	24	5.6	159	—	—	—	—	850	386	2500	1134
2730	Low-load/stand-up toggle**	2 7/8	73	2 1/4	57	1 9/16	24	5.12	145	3/16	5	5/32	4	500	227	2500	1134
2731	Stand-up toggle	2 7/8	73	2 1/4	57	1 9/16	24	5.12	145	3/16	5	5/32	4	850	386	2500	1134
2732	Low-load/loop**	2 7/8	73	2 1/4	57	1 9/16	24	4	113	—	—	—	—	500	227	2500	1134
2733	Loop	2 7/8	73	2 1/4	57	1 9/16	24	4	113	—	—	—	—	850	386	2500	1134
2734	Fixed sheaves/adjustable arms/365 Carbo-Cam	6 3/4	171	3 1/8	80	1 9/16	24	14.88	422	—	—	—	—	850	386	2500	1134
2735*	High-load/pivoting toggle	4 1/8	105	2 1/4	57	1 9/16	24	6.72	191	1/4	6	5/32	4	1250	567	2500	1134
2736	High-load/fixed sheaves/eyestraps	4 1/8	105	2 1/4	57	1 9/16	24	7.04	200	—	—	—	—	1250	567	2500	1134
2737	High-load/pivoting sheaves/eyestraps	4 1/8	105	2 1/4	57	1 9/16	24	9.6	272	—	—	—	—	1250	567	2500	1134
2738	High-load/pivoting sheaves/swivel/365 Carbo-Cam	4 1/8	105	6 1/8	156	1 9/16	24	19.84	562	—	—	—	—	1250	567	2500	1134
2753	Low-load/pivoting shackle/control tangs**	2 7/8	73	2 1/4	57	1 9/16	24	5.28	150	—	—	3/16	5	500	227	2500	1134
2754*	Pivoting shackle/control tangs	2 7/8	73	2 1/4	57	1 9/16	24	5.28	150	—	—	3/16	5	850	386	2500	1134
2756	Pivoting sheaves/471 Carbo-Cam	2 7/8	73	2 1/4	57	1 9/16	24	9.84	279	—	—	—	—	850	386	2500	1134
2757	High-load/pivoting sheaves/365 Carbo-Cam/eyestraps	4 1/8	105	2 1/4	57	1 9/16	24	14.18	401	—	—	—	—	1250	567	2500	1134

*Available as a non-CB car on a car loader to run on a non-CB style track supplied before 2002. Add .NW to end of part number.

**Small Boat low-load cars with a 227 kg (500 lb) maximum working load use Delrin® balls. See page 33 for replacement balls.

†For horizontal curved track only—600–800 mm (24"–40") radius. This car cannot be modified to run on old-style track made before 2003.