

75 mm Blocks

About Black Magic Air blocks: see feature pages at beginning of this section.



The low-load block has a red isolator. It uses Delrin® ball bearings, with a 17-4 PH stainless headpost and 316 stainless steel shackles.

O Yacht Class 4, 13.99 m (46'), O Yachts, naval architect: Lerouge © Daniel Levy / O Yachts



Delrin is a registered trademark of E. I. du Pont de Nemours and Company or its affiliates.

Part No.	Description	Sheave		Length		Weight		Shackle pin		Max line		Maximum working load		Breaking load	
		Ø	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg
3230	Single loop*	75	3 ¹⁵ / ₁₆	100	7.36	209	—	—	9/16	14	5000	2268	10000	4536	
3231	Single/swivel	75	5/8	129	11.68	331	5/16	8	9/16	14	5000	2268	10000	4536	
3232	Single/swivel/becket	75	6 ⁹ / ₁₆	157	12.8	363	5/16	8	9/16	14	5000	2268	10000	4536	
3233	Double/swivel	75	5/4	134	25.44	721	3/8	10	9/16	14	7500	3402	15000	6804	
3241	Spriddle/swivel	75/57	7 ¹³ / ₁₆	199	17.76	503	5/16	8	9/16	14	5000	2268	10000	4536	
3242	Spriddle/becket/swivel	75/57	8 ⁷ / ₁₆	225	18.96	538	5/16	8	9/16	14	5000	2268	10000	4536	
3243	Single/swivel/low-load	75	5/8	129	11.82	335	5/16	8	9/16	14	3000	1361	6000	2722	
3244	Stand-up**	75	5 ¹⁵ / ₁₆	151	15.6	442	—	—	9/16	14	5000	2268	10000	4536	

*Loop not included. See page 109. **Includes padeye. Uses hole spacing and base dimensions of 627 padeye. Maximum working load decreases at varying angles, refer to page 107.