

Jib Leads & Fairleads


Bolt-Down Fairleads

Harken Bolt-Down Fairleads are used as shallow-angle line deflectors on boats 6 - 15 m (20 - 50'). These weight-saving fairleads are built of 6061-T6 Hard Lube-anodized aluminum for durability. Smooth surfaces and radiused center holes minimize line wear.

Bolt-Down Fairleads are available in single, double, and triple configurations with 12 or 16 mm hole sizes.

Grand Prix Jib Leads

Strong aluminum jib leads deflect jib sheets to winches, preventing overrides. These jib leads have two small drilled holes through which a loop can be spliced to attach the hobbler. This temporarily secures the jib/genoa clew to free-up a winch for mark roundings.



Fastener spacing



TECH TIP

Hex-head bolts are ideal for one-person through-deck fastening as the hexagonal head is held securely by the sides of the inset when being tightened.

3274



3275



3276



3277



3278



3279



3280
3281



Baldur, Maxi 1200, 12.16 m (39.9'), Maxi Yachts, Delphia Yachts KOT, naval architect: Pelle Petterson © Nick Culley

| Part No. | Description | Length | | Width | | Height | | Max line Ø | | Weight | | Fasteners* | | A | Maximum working load | | Breaking load | |
|---------------------------|-------------------|---------------------------------|-----|--------------------------------|----|--------------------------------|------|--------------------------------|----|--------|-----|-----------------------------------|-------|------|----------------------|------|---------------|------|
| | | in | mm | in | mm | in | mm | in | mm | oz | g | in | mm | | mm | lb | kg | lb |
| Bolt-Down Fairlead | | | | | | | | | | | | | | | | | | |
| 3274 | Single/12 mm hole | 1 ⁷ / ₈ | 48 | 1 ¹ / ₁₆ | 18 | 1 ¹ / ₈ | 28.2 | 3 ³ / ₈ | 10 | .99 | 28 | 1 ¹ / ₄ | 6 | 32.0 | 2000 | 908 | 4000 | 1816 |
| 3275 | Double/12 mm hole | 2 ⁷ / ₈ | 74 | 1 ¹ / ₁₆ | 18 | 1 ¹ / ₈ | 28.2 | 3 ³ / ₈ | 10 | 1.73 | 49 | 1 ¹ / ₄ | 6 | 57.4 | 2000 | 908 | 4000 | 1816 |
| 3276 | Triple/12 mm hole | 3 ⁷ / ₈ | 99 | 1 ¹ / ₁₆ | 18 | 1 ¹ / ₈ | 28.2 | 3 ³ / ₈ | 10 | 2.43 | 69 | 1 ¹ / ₄ | 6 | 82.8 | 2000 | 908 | 4000 | 1816 |
| 3277 | Single/16 mm hole | 2 ³ / ₈ | 60 | 7 ⁷ / ₈ | 22 | 1 ¹ / ₄ | 31.8 | 9 ¹ / ₁₆ | 14 | 1.66 | 47 | 5 ¹ / ₁₆ | 8 | 37.0 | 4000 | 1816 | 8000 | 3632 |
| 3278 | Double/16 mm hole | 3 ⁹ / ₁₆ | 91 | 7 ⁷ / ₈ | 22 | 1 ¹ / ₄ | 31.8 | 9 ¹ / ₁₆ | 14 | 2.82 | 80 | 5 ¹ / ₁₆ | 8 | 67.5 | 4000 | 1816 | 8000 | 3632 |
| 3279 | Triple/16 mm hole | 4 ³ / ₄ | 121 | 7 ⁷ / ₈ | 22 | 1 ¹ / ₄ | 31.8 | 9 ¹ / ₁₆ | 14 | 3.95 | 112 | 5 ¹ / ₁₆ | 8 | 98.0 | 4000 | 1816 | 8000 | 3632 |
| Jib lead | | | | | | | | | | | | | | | | | | |
| 3280 | Midrange | 2 ¹⁵ / ₁₆ | 75 | 7 ⁷ / ₈ | 22 | 1 ⁷ / ₁₆ | 37 | 1 ¹ / ₂ | 12 | 2.97 | 84 | 1 ¹ / ₄ | 6 | 55.0 | 1500 | 680 | 3000 | 1360 |
| 3281 | Big Boat | 4 ¹⁵ / ₁₆ | 125 | 1 ¹ / ₈ | 29 | 2 ⁵ / ₁₆ | 58 | 7 ⁷ / ₈ | 22 | 9.72 | 276 | 7 ¹ / ₁₆ ** | 10*** | 96.0 | 4250 | 1930 | 8500 | 3860 |

*HH, SH, CH in 6 mm, 5/16" and 8 mm. Size 1/4" in SH only. **7/16" in HH and SH. ***10 mm in HH, SH and CH.
DO NOT use Harken equipment for human suspension unless product is specifically certified and labeled for such use.