




5. Winches

EVO® Speed Ring Winch

EVO® Speed Ring racing winches offer all the features of the EVO® Range with the additional benefit of two drum diameters. The larger drum is used for fast asymmetric spinnaker gybes or hoists while the standard size drum allows fine tuning, removing the need for additional winches.

- Easy servicing – no tools required
- Available in black or grey alloy finish
- Features two drum diameters for greater control



EVO® Speed Ring Winch Specifications

| PART NO | SIZE | FINISH | GEAR RATIO | | POWER RATIO | | SPEED RING POWER RATIO | | WLL | | WEIGHT | | D DRUM DIA | | S SPEED RING DIA | | B BASE DIA | | H HEIGHT | | L LINE ENTRY | | LINE SIZE | |
|----------|------|--------|------------|-------|-------------|--------|------------------------|--------|------|------|--------|------|----------------------|---------------------------------|----------------------------|-------------------------------|----------------------|---------------------------------|--------------------|-------------------------------|------------------------|--------------------------------|-----------|---|
| | | | 1st | 2nd | 1st | 2nd | 1st | 2nd | kg | lb | kg | lb | mm | in | mm | in | mm | in | mm | in | mm | in | mm | in |
| 49540085 | 40 | Black | 1.9:1 | 5.8:1 | 13.2:1 | 40.2:1 | 6.6:1 | 20.3:1 | 795 | 1753 | 4.9 | 10.7 | 74 | 2 ¹⁵ / ₁₆ | 145.5 | 5 ³ / ₄ | 148 | 5 ¹³ / ₁₆ | 158.5 | 6 ¹ / ₄ | 79 | 3 ¹ / ₈ | 8-12 | 5 ¹ / ₁₆ -1 ¹ / ₂ |
| 49540087 | 40 | Grey | 1.9:1 | 5.8:1 | 13.2:1 | 40.2:1 | 6.6:1 | 20.3:1 | 795 | 1753 | 4.9 | 10.7 | 74 | 2 ¹⁵ / ₁₆ | 145.5 | 5 ³ / ₄ | 148 | 5 ¹³ / ₁₆ | 158.5 | 6 ¹ / ₄ | 79 | 3 ¹ / ₈ | 8-12 | 5 ¹ / ₁₆ -1 ¹ / ₂ |
| 49545085 | 45 | Black | 2.36:1 | 8.0:1 | 13.86:1 | 46.8:1 | 7:1 | 22.6:1 | 1200 | 2643 | 7.6 | 16.7 | 86.8 | 3 ⁷ / ₁₆ | 170.5 | 6 ³ / ₄ | 205 | 8 | 177.5 | 7 | 84.5 | 3 ³ / ₁₆ | 8-12 | 5 ¹ / ₁₆ -1 ¹ / ₂ |
| 49545087 | 45 | Grey | 2.36:1 | 8.0:1 | 13.86:1 | 46.8:1 | 7:1 | 22.6:1 | 1200 | 2643 | 7.6 | 16.7 | 86.8 | 3 ⁷ / ₁₆ | 170.5 | 6 ³ / ₄ | 205 | 8 | 177.5 | 7 | 84.5 | 3 ³ / ₁₆ | 8-12 | 5 ¹ / ₁₆ -1 ¹ / ₂ |

Lewmar Evo Race+™ Winch

Lewmar's EVO Race+ winches use a lightweight cast aluminium base stem and machined aluminium upper stem, together with other advanced material choices, to offer significant weight savings over standard EVO® winches.

- Lightweight centre stem
- Lightened main spindle
- Lightweight cast aluminium feeder arm
- Composite bearing technology
- "No tools" servicing
- Carbon fibre inlay
- Silver trim stripe
- White pad-printed decals.
- Black anodised drum



EVO® Race+™ Self-Tailing Winch Specifications

| PART NO | SIZE | GEAR RATIO | | POWER RATIO | | WLL | | WEIGHT | | D DRUM DIA | | B BASE DIA | | H HEIGHT | | L LINE ENTRY | | LINE SIZE | |
|----------|------|------------|--------|-------------|--------|------|------|--------|------|----------------------|---------------------------------|----------------------|---------------------------------|--------------------|---------------------------------|------------------------|--------------------------------|-----------|--|
| | | 1st | 2nd | 1st | 2nd | kg | lb | kg | lb | mm | in | mm | in | mm | in | mm | in | mm | in |
| 49940055 | 40ST | 1.9:1 | 5.8:1 | 13.2:1 | 40.2:1 | 795 | 1753 | 3.6 | 7.9 | 74 | 2 ¹⁵ / ₁₆ | 148 | 5 ¹³ / ₁₆ | 158.5 | 6 ¹ / ₄ | 79 | 3 ¹ / ₈ | 8-12 | 5 ¹ / ₁₆ -1 ¹ / ₂ |
| 49945055 | 45ST | 2.4:1 | 7.6:1 | 13.9:1 | 44.8:1 | 1200 | 2646 | 4.8 | 10.5 | 87 | 3 ⁷ / ₁₆ | 168 | 6 ⁵ / ₈ | 177.7 | 7 | 84 | 3 ⁵ / ₁₆ | 8-14 | 5 ¹ / ₁₆ -9 ¹ / ₁₆ |
| 49950055 | 50ST | 2.6:1 | 9:1 | 13.9:1 | 48.6:1 | 1250 | 2756 | 6.3 | 13.9 | 93 | 3 ⁵ / ₈ | 181 | 7 ¹ / ₈ | 197 | 7 ³ / ₄ | 90 | 3 ¹ / ₂ | 8-14 | 5 ¹ / ₁₆ -9 ¹ / ₁₆ |
| 49955055 | 55ST | 2.8:1 | 11.2:1 | 13.8:1 | 54:1 | 1480 | 3263 | 8.3 | 18.3 | 105 | 4 ¹ / ₈ | 205 | 8 ¹ / ₁₆ | 250 | 9 ¹³ / ₁₆ | 115 | 4 ¹ / ₂ | 8-16 | 5 ¹ / ₁₆ -5 ¹ / ₈ |