




7. Hardware

Ocean/NTR Size 1, 2 and 3 Tracks


Beam track



Beam track is used when spanning cockpits and across companion way hatches. Three fixing bolts should always be used either side of the span and washers fitted under the head of the bolt and between track and deck. Some beam track can only use metric fasteners

Made of Aluminium 6082T6 extrusion


Sliding bolt Track



Sliding bolt track have a smooth clean profile with no visible fixings and can be retro-fitted using original bolt holes – no need to worry about old track pattern holes matching up with a new track. The track is designed to permit a washer to fit on each bolt between the track and deck to ensure a secure seal.

Grey anodised finish

Drilled Plunger Track



Commonly used and particularly useful where through deck fixing is not possible, such as in double skinned boats, where fixing bolts are trapped into a plate in the deck.

Ocean/NTR Size 1, 2 & 3 Track Specifications and Fixing Details

PART NO	DESCRIPTION	TRACK SIZE	LENGTH		HEIGHT		WIDTH		WEIGHT (per metre)		MAX SPAN BETWEEN FIXINGS / CENTRE HOLE DIM		FIXINGS	
			m	ft	mm	in	mm	in	g	oz	mm	in	Metric	Imperial
29162315BK	Beam Track	2	1.5	4'11"	35	1.38	35	1.38	1560	54.91	800	31 1/2	Hex Hd M10	-
29162320BK			2	6'7"										
29163315BK	Beam Track	3	1.5	4'11"	55	2.16	50	1.97	3640	128.13	900	35 7/16	Hex Hd M12	-
29163320BK			2	6'7"										
29163330BK			3	9'10"										
29161510BK	HD Beam Track	1	1	3'3"	42	1.75	32	1.25	1770	62.4	900	35 7/16	Hex Hd M8	5/16"
29161515BK			1.5	4'11"										
29161520BK	HD Beam Track	2	2	6'7"	51	2	51	2	3000	105.82	900	35 7/16	Hex Hd M10	3/8"
29162515BK			1.5	4'11"										
29162520BK	HD Beam Track	2	2	6'7"	51	2	51	2	3000	105.82	900	35 7/16	Hex Hd M10	3/8"
29162115BK			1.5	4'11"										
29162120BK	Sliding Bolt Track	2	2	6'7"	18	0.71	30	1.18	839	29.56	800	31 1/2	Hex Hd M8	5/16"
29162130BK			3	9'10"										
29161415BK	Drilled Plunger Track	1	1.526	5'	13	0.5	23	0.9	530	18.65	100	3 15/16	Hex Hd M6	1/4"
29161420BK			2.026	6'8"										
29161430BK			3.026	9'11"										
29162415BK	Drilled Plunger Track	2	1.532	5'	15	0.56	30	1.18	764	26.95	100	3 15/16	Hex Hd M8	5/16"
29162420BK			2.032	6'3"										
29162430BK			3.032	10'										
29163615BK	Drilled Plunger Track	3	1.548	5'1"	21	0.84	35	1.38	968	33.88	100	3 15/16	Hex Hd M10	3/8"
29163620BK			2.048	6'9"										
29163630BK			3.048	10'1"										

M12

