


Flat & Curved Base Cheek Blocks

Flat Base Cheek Blocks

Flat, stainless base plate distributes loads to a larger surface area than other designs that place loads on mounting bolts only. Use on spars and deck to lead sheets, halyards, reefing gear, and any control requiring a strong, smooth lead.



30-27



504-11



706-11



504-28



705-10

Item Stain.	Item Alum.	Item Ball Brg.	Descrip.	Sheave Dia.	Max Line	L	W	H	Fasteners	C/C	SWL	Weight Stain.	Weight Alum.
30-27	303-09	300-09	Flat Base/Sngl/Delrin™	1-7/16" (37mm)	7/16" (11mm)	2-7/8" (73mm)	1-3/4" (44mm)	3/4" (19mm)	(4) #10 RH (5mm)	2-3/8" (60mm)	1000 lbs. (450kg)	2.6 oz. (74g)	2.5 oz. (71g)
---	303-29	---	Flat Base/Dbl/Delrin™	1-7/16" (37mm)	7/16" (11mm)	2-7/8" (73mm)	1-3/4" (44mm)	1-7/16" (37mm)	(4) #10 RH (5mm)	2-3/8" (60mm)	1000 lbs.** (450kg)	---	4.2 oz. (119g)
505-11	504-11	506-11	Flat Base/Sngl/Delrin™	2" (51mm)	7/16" (11mm)	3-5/8" (92mm)	2-7/32" (57mm)	7/8" (22mm)	(4) #10 RH (5mm)	3" (76mm)	1750 lbs.* (795kg)	6.9 oz. (196g)	5.9 oz. (167g)
505-10	504-10	---	Flat Base/Sngl/Alum.	2" (51mm)	7/16" (11mm)	3-5/8" (92mm)	2-7/32" (57mm)	7/8" (22mm)	(4) #10 RH (5mm)	3" (76mm)	1750 lbs. (795kg)	7.5 oz. (213g)	6.5 oz. (184g)
505-28	504-28	---	Flat Base/Dbl/Delrin™	2" (51mm)	7/16" (11mm)	3-5/8" (92mm)	2-7/32" (57mm)	1-19/32" (40mm)	(4) #10 RH (5mm)	3" (76mm)	1750 lbs.** (795kg)	10.7 oz. (303g)	7.9 oz. (224g)
705-11	704-11	706-11	Flat Base/Sngl/Delrin™	2-3/8" (60mm)	1/2" (13mm)	4-3/8" (111mm)	2-3/4" (70mm)	1" (25mm)	(4) 1/4" RH (6mm)	3-5/8" (92mm)	2250 lbs.* (1020kg)	11 oz. (312g)	9.6 oz. (272g)
705-10	704-10	---	Flat Base/Sngl/Alum.	2-3/8" (60mm)	1/2" (13mm)	4-3/8" (111mm)	2-3/4" (70mm)	1" (25mm)	(4) 1/4" RH (6mm)	3-5/8" (92mm)	2250 lbs. (1020kg)	12.4 oz. (351g)	11.0 oz. (312g)
705-28	704-28	---	Flat Base/Dbl/Delrin™	2-3/8" (60mm)	1/2" (13mm)	4-3/8" (111mm)	2-3/4" (70mm)	1-29/32" (48mm)	(4) 1/4" RH (6mm)	3-5/8" (92mm)	2250 lbs.** (1020kg)	15.8 oz. (447g)	13 oz. (368g)

* SWL for 506-11, 1500 lbs. (680kg), 706-11, 1700 lbs. (771kg) ** SWL for Top Sheave of double version 303-29, 200 lbs. (91kg), 504-28/505-28, 350 lbs. (159kg), and 704-28/705-28, 500 lbs. (227kg)

Curved Base Cheek Blocks

Unique curved base plate fits up to 2" (51mm) dia. spar section for easy mounting. Excellent for control line leads on dinghys and small daysailors.



03-30



200-30

Item Stain.	Item Alum.	Item Ball Brg.	Descrip.	Sheave Dia.	Max Line	L	W	H	Fasteners	C/C	SWL	Weight Stain.	Weight Alum.
30-04	---	200-30*	Curved/Base Sngl/Delrin™	1-1/16" (27mm)	5/16" (8mm)	3-1/2" (89mm)	1" (25mm)	21/32" (17mm)	(4) #10 RH (5mm)	3" (76mm)	900 lbs.* (410kg)	1.5 oz. (42g)	---
03-30	303-30	300-30	Curved/Base Sngl/Delrin™	1-7/16" (37mm)	7/16" (11mm)	3-11/16" (949mm)	1" (25mm)	3/4" (19mm)	(4) #10 RH (5mm)	3-3/16" (94mm)	1000 lbs.* (450kg)	2.2 oz. (62g)	2.1 oz. (2.1 oz.)

*SWL for 200-30 is 500 lbs (225kg)

Cheek Block Pad

Choose pad to work with 5 or 7 Series

Item	Descrip.	Mounts to / Works With	Weight
55-60	5 Series Cheek Pad	Fits 2-1/2" to 6" dia. spar section. (64mm-152mm)	1.5 oz. (43g)
55-61	7 Series Cheek Pad	Fits 3" to 7" dia. spar section. (76mm-178mm)	2 oz. (57g)