

Over The Top Blocks

Polished and Tumbled Stainless Steel Cage and Delrin™ Ball Bearings provide an ingenious solution for difficult leads.



706-40

Over-the-Top Blocks

Designed to bring control lines over the forward edge of cabin houses, coamings or rails. Perfect for Raised Salon designs. Low Friction ball bearing sheaves lead lines easily.



300-40

300-41

300-42



506-40

506-41

506-42

Item	Descrip. Sheave	Sheave Dia	Max Line	L	W	H	Bearing Height	Fasteners	C/C	SWL	Weight
300-40	Over The Top Single / BB	1-7/16" (37mm)	7/16" (11mm)	2-11/32" (60mm)	2" (51mm)	2-11/32" (60mm)	1-13/32" (36mm)	(6)#10 RH (5mm)	1-25/32" (45mm)	650 lbs. (295kg)	4.7 oz. (133g)
300-41	Over The Top Double / BB	1-7/16" (37mm)	7/16" (11mm)	2-11/32" (60mm)	2-11/16" (68mm)	2-11/32" (60mm)	1-13/32" (36mm)	(6)#10 RH (5mm)	1-25/32" (45mm)	650 lbs. (295kg)	7.2 oz. (204g)
300-42	Over The Top Triple / BB	1-7/16" (37mm)	7/16" (11mm)	2-11/32" (60mm)	3-3/8" (86mm)	2-11/32" (60mm)	1-13/32" (36mm)	(6)#10 RH (5mm)	1-25/32" (45mm)	650 lbs. (295kg)	10.0 oz. (328g)
506-40	Over The Top Single / BB	2" (51mm)	7/16" (11mm)	2-7/8" (73mm)	2-1/16" (52mm)	2-15/16" (74mm)	2" (51mm)	(6)#10 RH (5mm)	2-5/16" (59mm)	1000 lbs. (450kg)	8.4 oz. (283g)
506-41	Over The Top Double / BB	2" (51mm)	7/16" (11mm)	2-7/8" (73mm)	2-3/4" (76mm)	2-15/16" (74mm)	2" (51mm)	(6)#10 RH (5mm)	2-5/16" (59mm)	1000 lbs. (450kg)	12.6 oz. (357g)
506-42	Over The Top Triple / BB	2" (51mm)	7/16" (11mm)	2-7/8" (73mm)	3-17/32" (90mm)	2-15/16" (74mm)	2" (51mm)	(6)#10 RH (5mm)	2-5/16" (59mm)	1000 lbs. (450kg)	1 lb. 1 oz. (482g)
706-40	Over The Top Single / BB	2-3/8" (60mm)	1/2" (13mm)	3-3/8" (86mm)	2-1/4" (57mm)	3-7/16" (87mm)	2-5/16" (58mm)	(6)#10 RH (5mm)	2-13/16" (72mm)	1200 lbs. (545kg)	11.6 oz. (329g)
706-41	Over The Top Double / BB	2-3/8" (60mm)	1/2" (13mm)	3-3/8" (86mm)	3-5/32" (80mm)	3-7/16" (87mm)	2-5/16" (58mm)	(6)#10 RH (5mm)	2-13/16" (72mm)	1200 lbs. (545kg)	1 lb. 2 oz. (510g)
706-42	Over The Top Triple / BB	2-3/8" (60mm)	1/2" (13mm)	3-3/8" (86mm)	4-1/16" (104mm)	3-7/16" (87mm)	2-5/16" (58mm)	(6)#10 RH (5mm)	2-13/16" (72mm)	1200 lbs. (545kg)	1 lb. 8.4 oz. (692g)