

Stainless Hardware

Investment Cast Pad Eyes

These heavy-duty pad eyes are investment cast from high quality Stainless Steel for a high degree of accuracy and strength. The first step in this process involves making a wax part from a master or permanent die. The wax part is then used in a temporary or series of temporary molds. The actual parts are then cast from the molds without any wear to the permanent die to ensure accurate casting each time. Backing Plates are from high quality stainless steel and are sold separately. Refer to chart below for ordering information.

Safe Working Loads are based upon proper mounting. Please contact Schaefer for more information.

Schaefer x-rays all of our investment cast pad eyes to ensure a safe finished product is on your boat.



78-17



78-96



78-98



97-42

Item	Descrip.	Backing Plate	Eye Width	Eye Height	Eye Stock	L	W	Fasteners	C/C A	C/C B	SWL	Weight
78-07	Inv. Cast/ Rnd Base	97-53	1" (25mm)	13/16" (21mm)	3/8" (10mm)	2-1/2" (64mm)	2-1/2" (64mm)	(4) 1/4" (FH6mm)	1" (25mm)	1-1/2" (38mm)	4000 lbs. (1800kg)	4 oz. (113g)
78-17	Inv. Cast/ Rnd Base	97-54	1-1/8" (29mm)	7/8" (22mm)	1/2" (13mm)	3" (76mm)	3" (76mm)	(4) 3/8" (FH10mm)	1-1/8" (29mm)	1-11/16" (43mm)	8500 lbs. (3800kg)	12 oz. (340g)
78-95	Inv. Cast/ Diamd. Base	97-57	3/4" (19mm)	7/16" (11mm)	5/16" (8mm)	3-1/8" (79mm)	2" (4) (51mm)	(4) 1/4" (FH6mm)	2-13/32" (61mm)	1-1/4" (32mm)	4000 lbs. (1800kg)	5 oz. (142g)
78-96	Inv. Cast/ Diamd. Base	97-56	1" (25mm)	5/8" (16mm)	3/8" (10mm)	4" (102mm)	2-3/8" (4) (60mm)	(4) 1/4" (FH6mm)	3" (76mm)	1-9/16" (40mm)	4400 lbs. (2000kg)	8.5 oz. (241g)
78-98	Inv. Cast/ Oblong Base	97-58	5/8" (16mm)	1/2" (13mm)	5/16" (8mm)	3" (76mm)	15/16" (24mm)	(2) 1/4" (FH6mm)	2-3/32" (53mm)	---	2200 lbs. (1000kg)	4 oz. (113g)
78-99	Inv. Cast/ Oblong Base	78-26	7/8" (22mm)	3/4" (19mm)	7/16" (11mm)	4" (102mm)	1-3/8" (35mm)	(2) 5/16" (FH8mm)	2-7/8" (73mm)	---	3500 lbs. (1600kg)	10 oz. (284g)
97-42	Inv. Cast/ Sqr Base	97-52	3/4" (19mm)	3/4" (19mm)	5/16" (8mm)	3" (76mm)	3" (76mm)	(4) 1/4" (FH6mm)	2" (51mm)	2" (51mm)	4000 lbs. (1800kg)	11 oz. (312g)

If you are in doubt as to the suitability of your selection please contact Schaefer for assistance.

Bow Eye / Lifting Ring

Choose from our Stainless Steel Bow Eye or Lifting Ring for applications requiring a high quality attachment.



78-22



78-71

Item	Descrip.	Eye Width	Eye Height	Eye Stock	L	W	Fasteners	C/C A	C/C B	SWL	Weight
78-71	Bow Eye/ Cvrd. Base*	3/4" (19mm)	1/2" (13mm)	1/4" (6mm)	1-3/4" (44mm)	5/8" (16mm)	1" 1/4-20 Rod (25mm, 6mm)	1" (25mm)	---	2000 lbs. (900kg)	1.75 oz. (50g)
78-22	Lifting Ring/ Strap Base	1-3/8" (35mm)	1-3/8" (35mm)	5/16" (8mm)	3-1/2" (92mm)	3/4" (16mm)	(4) #10 FH (5mm)	2-3/4" (48mm)	11/16" (19mm)	1000 lbs. (450kg)	4 oz. (113g)

*Stainless bow eye has curved base to fit small boat stems.