

Genoa Blocks

Spring Loaded Blocks on Slides

Spring loaded blocks offer a wide flexibility in sheeting angles allowing for up to a 45° lead variation to each side of the track. "Spring Cap" design fully supports blocks under any conditions. 1" and 1-1/4" versions feature polyethylene liners held "captive" within the slide allowing for years of trouble free and friction free service. Choose from brilliant Stainless Steel or Hardcoat Anodized Aluminum cheeks both using UV resistant Delrin™ sheaves. Our New M66-92 features an Aluminum Sheave with Torlon™ Rollers and Delrin™ Ball Bearings for smooth sheeting. Center Hub may be used as a becket to create a 2:1 jib sheet purchase.



03-72




303-72



03-86



303-86



505-82



504-82

Item	Descrip.	Track Size	Boat Size Up To* LOA, Displ., Sail Area	Sheave Dia.	Max Line	L	W	H	Bearing Height	SWL	Weight
03-72	Spr. Loaded S.S.	3/4" x 1/8" (19mm x 3mm)	20', 2000 lbs., 225 sq. ft. (6m, 910kg, 21m2)	1-7/16" (60mm)	7/16" (11mm)	2-1/2" (64mm)	31/32" (25mm)	3-17/32" (90mm)	2-5/32" (55mm)	1000 lbs. (450kg)	4.5 oz. (113g)
303-72	Spr. Loaded Alum.	3/4" x 1/8" (19mm x 3mm)	20', 2000 lbs., 225 sq. ft. (6m, 910kg, 21m2)	1-7/16" (60mm)	7/16" (11mm)	2-1/2" (64mm)	31/32" (25mm)	3-17/32" (90mm)	2-5/32" (55mm)	1000 lbs. (450kg)	4.0 oz. (113g)
03-86	Spr. Loaded/Lined Slide/S.S.	1" x 1/8" (25mm x 3mm)	27', 5000 lbs., 315 sq. ft. (8m, 2270kg, 29m2)	1-7/16" (60mm)	7/16" (11mm)	3" (76mm)	1-1/4" (31mm)	3-17/32" (90mm)	2-5/32" (55mm)	1000 lbs. (450kg)	4.5 oz. (128g)
303-86	Spr. Loaded/Lined Slide/Alum.	1" x 1/8" (25mm x 3mm)	27', 5000 lbs., 315 sq. ft. (8m, 2270kg, 29m2)	1-7/16" (60mm)	7/16" (11mm)	3" (76mm)	1-1/4" (31mm)	3-17/32" (90mm)	2-5/32" (55mm)	1000 lbs. (450kg)	4.0 oz. (113g)
505-82	Spr. Loaded/Lined Slide/S.S.	1" x 1/8" (25mm x 3mm)	27', 5000 lbs., 315 sq. ft. (8m, 2270kg, 29m2)	2" (51mm)	7/16" (11mm)	3" (76mm)	1-1/4" (31mm)	4-5/32" (105mm)	2-7/32" (56mm)	1750 lbs. (795kg)	6.5 oz. (184g)
504-82	Spr. Loaded/Lined Slide/Alum.	1" x 1/8" (25mm x 3mm)	27', 5000 lbs., 315 sq. ft. (8m, 2270kg, 29m2)	2" (51mm)	7/16" (11mm)	3" (76mm)	1-1/4" (31mm)	4-5/32" (105mm)	2-7/32" (56mm)	1750 lbs. (795kg)	7.0 oz. (198g)
705-92	Spr. Loaded/Lined Slide/S.S.	1-1/4" x 3/16" (32mm x 5mm)	33', 12000 lbs., 520 sq. ft. (10m, 5455kg, 48m2)	2-3/8" (60mm)	1/2" (12mm)	4" (102mm)	1-9/16" (39mm)	4-15/16" (126mm)	2-5/8" (67mm)	2250 lbs. (1020kg)	14 oz.z. (397g)
704-92	Spr. Loaded/Lined Slide/Alum.	1-1/4" x 3/16" (32mm x 5mm)	33', 12000 lbs., 520 sq. ft. (10m, 5455kg, 48m2)	2-3/8" (60mm)	1/2" (12mm)	4" (102mm)	1-9/16" (39mm)	4-15/16" (126mm)	2-5/8" (67mm)	2250 lbs. (1020kg)	12 oz. (340g)
08-92	Spr. Loaded/Lined Slide/S.S.	1-1/4" x 3/16" (32mm x 5mm)	38', 18000 lbs., 715 sq. ft. (11.5m, 8182kg, 66m2)	2-3/8" (60mm)	9/16" (14mm)	4" (102mm)	1-9/16" (39mm)	4-7/8" (124mm)	2-23/32" (69mm)	2750 lbs. (1250kg)	1 lb. (454g)
M66-92	Spr. Loaded/Lined Slide/Alum.	1-1/4" x 3/16" (32mm x 5mm)	38', 18000 lbs., 715 sq. ft. (11.5m, 8183kg, 66m2)	2-5/8" (66mm)	1/2" (12mm)	4" (102mm)	1-9/16" (39mm)	5-1/2" (140mm)	3" (76mm)	2800 lbs. (1270kg)	1 lb. (454gm)

Replacement liners for 1" = 25-287. Replacement liner for 1-1/4" = 25-286



705-92



704-92



08-92



M66-92